



Adhesive Specialities Ltd
Tickitape House, 31 Bone Lane
Newbury, RG14 5SH
+44(0)1635 49825

TECHNICAL DATA SHEET

20/3/14

REF: AS 239AV Low Tack PVC Protection Tape

DESCRIP: A 130 micron high strength black PVC based tape that combines a flexible PVC backing with a pressure sensitive adhesive. High resistance to corrosion, UV, moisture and chemicals.

| | | |
|--------------|------------------------------|--|
| SPEC: | <u>Widths Available:</u> | Sizes upon request |
| | <u>Standard Length:</u> | 33m other sizes available upon request |
| | <u>Colours</u> | Various colours |
| | <u>Thickness:</u> | 130µm ±10% |
| | <u>Film:</u> | PVC |
| | <u>Adhesive:</u> | Pressure sensitive rubber adhesive |
| | <u>Elongation:</u> | 200% |
| | <u>Tensile strength:</u> | 2.5 kg/cm |
| | <u>Dielectric breakdown:</u> | 6,500 (Volts) |
| | <u>Dielectric Strength:</u> | 1,250 (Volts/mil) |

STORAGE: The tape should be protected against dust and extreme humidity and can be stored under normal room conditions (+8 to 35°C) for maximum of 12 months

USES: Protection of most substrates. Industrial applications. Electrical insulation. The tape protects the surface against the degradations caused by dirt, the scratches and the sings of utensils during the complete cycle of its usage: maintenance, storage, transportation and assembly. It does NOT protect against corrosion, humidity or chemical substances. This tape is not suitable for extreme Thermo-forming.

APPLICATION: Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to always satisfy themselves as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.