



Adhesive Specialities Ltd
Tickitape House, 31 Bone Lane
Newbury, RG14 5SH
+44(0)1635 49825

TECHNICAL DATA SHEET

04/12/13

REF: AS 249TT Glazing Pads Blue

DESCRIP: A blue unsupported vinyl foam coated with a special low tack pressure sensitive adhesive.

SPEC:	<u>Stock Sizes:</u>	19mm x 25mm
	<u>Nominal Thickness:</u>	4.0mm
	<u>Colour:</u>	Blue only
	<u>Density:</u>	260 - 290 Kg/m ³
	<u>Tensile Strength:</u>	0.5 Mpa min.
	<u>Elongation:</u>	150% min.
	<u>Tear Strength:</u>	2.5 Kg/cm min.
	<u>Shore Hardness:</u>	55 – 80
	<u>Adhesion to Steel:</u>	.625 N/25cm
	<u>Service Temperature:</u>	-20° C to +50° C
	<u>Application Temperature:</u>	above 10° C

STORAGE: Normal room temperature

USES: These foam pads are specifically designed to separate and protect sealed units and glass when in storage or transit and then to remove cleanly.

APPLICATION: Surfaces to be bonded must be clean, dry and free from dust.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to always satisfy themselves as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.