



Adhesive Specialities Ltd
Tickitape House, 31 Bone Lane
Newbury, RG14 5SH
+44(0)1635 49825

TECHNICAL DATA SHEET

19/12/13

<u>REF:</u>	AS 119AV Glass Repair tape	
<u>SPEC:</u>	<u>Standard Widths:</u>	Standard others upon request
	<u>Length:</u>	Standard others upon request
	<u>Colour:</u>	Clear
	<u>Thickness:</u>	100 µm
	<u>Film Type:</u>	Polyethylene (LDPE)
	<u>Adhesive:</u>	Acrylic
	<u>Adhesion to steel:</u>	400 cN/cm
	<u>Tensile Strength:</u> Longitudinal	> 1.9 daN/cm
	Transversal	> 1.5 daN/cm
	<u>Elongation:</u> Longitudinal	>370%
	Transversal	>550%

STORAGE: The tape can be stored for max 6 months at room temperature, in dry conditions and its original packaging.

USES: Temporary protection of carpets and moquettes. Temporary holding of broken glass as a safety film.

APPLICATION: Surfaces to be bonded must be clean, dry and free from dust.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to always satisfy themselves as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.