



Adhesive Specialities Ltd
Tickitape House, 31 Bone Lane
Newbury, RG14 5SH
+44(0)1635 49825

TECHNICAL DATA SHEET

09/02/15

REF: AS 223SL Premium Cloth Tape

DESCRIP: A premium grade polythene laminated 45 mesh coated adhesive tape with high flexibility and conformability.

SPEC:	<u>Widths Available:</u>	On request mm –19 mm to 45 mm
	<u>Standard Length:</u>	50M
	<u>Colours Available:</u>	Black, Silver, White
	<u>Thickness:</u>	210µm
	<u>Backing Thickness:</u>	150µm
	<u>Mesh</u>	45
	<u>Tensile Strength:</u>	58.8 N/cm
	<u>Adhesion to steel:</u>	3.14 N/cm
	<u>Tack:</u>	22≤
	<u>Holding Power at 40°C:</u>	5 falling time (min)

STORAGE: Normal room temperature

USES: General purposes. Sealing ductwork joints, general purpose packing, packaging, bundling, sealing, jointing, repairing, strapping and identifying. Ideal for joining polythene sheeting and many other uses within the construction and the heating and ventilation industries.

APPLICATION: Clean surface from dirt, water or oil before applying the tape to obtain optimum adhesion. Press well after applying the tape. Store the tape at cool and dry place, and avoid direct sunlight or heat sources such as room heater etc. Do not use this tape as electric insulation. There is possibility for this tape to leave residue or to cause contamination to the surface, therefore do not apply directly to furniture, wall glass, PVC products, or car bodies or adhesive residues, discolouration or peeling of paint may arise. Please do not stick tapes directly to the skin unless the tapes are designed for this application, otherwise a rash or adhesive deposit may arise. Confirm carefully for the selection of tape before in order to avoid adhesive

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to always satisfy themselves as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.



Adhesive Specialities Ltd
Tickitape House, 31 Bone Lane
Newbury, RG14 5SH
+44(0)1635 49825

TECHNICAL DATA SHEET

residue and/or contamination to adherents that may arise by applications. Consult with ASL when use the tape for special applications or seem to use special applications.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to always satisfy themselves as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.