



Adhesive Specialities Ltd  
Tickitape House, 31 Bone Lane  
Newbury, RG14 5SH  
+44(0)1635 49825

## TECHNICAL DATA SHEET

<b>REF:</b>	AS 111AV Glass Protection Film	09/08/16
<b>DESCRIP:</b>	Temporary protection of sensitive surfaces (plastic profiles, rigid PVC sheets, precoated metal) against dirt and damage during processing, storage and mounting.	
<b>SPEC:</b>	<u>Widths available:</u>	Sizes upon request
	<u>Standard length:</u>	Sizes upon request
	<u>Colour:</u>	Blue transparent
	<u>Film Thickness (avg):</u>	35 µm
	<u>Film:</u>	UV treated polyolefin
	<u>Adhesive</u>	Acrylic
	<u>Adhesion to steel</u>	55 cN/cm
	<u>Unwinding Force</u>	<20 cN/cm
	<u>Tensile Strength</u> Longitudinal	>1.35 daN/cm
	Transversal	>0.9 daN/cm
	<u>Elongation</u> Longitudinal	>400%
	Transversal	>600%
<b>STORAGE:</b>	The tape can be stored for 6 months, in dry conditions, in its original packaging. Do not expose materials protected with tape to exterior conditions for more than 3 months.	
<b>USES:</b>	Easy peel film for temporary protection of surfaces for the following materials: glossy or half glossy materials such as pre-painted metal, acrylic sheets, polycarbonate, polystyrene, rigid PVC, cold rolled stainless, aluminium glass and decorative laminates. Not suitable for protection against corrosion, humidity or chemical solvents.	
<b>APPLICATION:</b>	Do not expose materials protected with tape to exterior conditions for than 3 months (Northern Europe only). For a good application, surface must be free from fat, oils, solvents, dust, and/or other extraneous substances. The film must be used without folds of bubbles and without excessive tension. The film protects the surface against the degradations caused by dirt, the scratches, during the maintenance, storage, transformation and assembly. The film does NOT protect against	

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.



**Adhesive Specialities Ltd**  
Tickitape House, 31 Bone Lane  
Newbury, RG14 5SH  
**+44(0)1635 49825**

## TECHNICAL DATA SHEET

corrosion, humidity or chemical substances. As the protection film can have several applications, product suitability may be verified only after user has satisfied himself as to suitability before the use.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.