



Adhesive Specialities Ltd
Tickitape House, 31 Bone Lane
Newbury, RG14 5SH
+44(0)1635 49825

TECHNICAL DATA SHEET

12/12/14

REF: AS 144PL Coloured Vinyl Tape

DESCRIP: A very strong PVC film coated with an aggressive solvent rubber pressure sensitive adhesive.

SPEC:

<u>Widths Available:</u>	9, 12, 19, 25, 38, 50, 75mm
<u>Standard Length:</u>	66m
<u>Colours:</u>	Blue, green, yellow, orange, black, red.
<u>Thickness:</u>	Film 40 µm Total 60 µm
<u>Adhesion to Steel:</u>	4.00 N/25mm
<u>Adhesion to Backing:</u>	6.50 N/25mm
<u>Tensile Strength (Backing):</u>	8.53 N/mm ²
<u>Elongation:</u>	140%
<u>Temperature resistance:</u>	Short term max. 80°C

STORAGE: Normal room temperature

USES: Used as a colour coding to identify packages. Narrow widths used in bag sealing machines. Also used for bookbinding. The tape is not suitable for use in direct with foods and in the first level of the indirect contact. The tape can be used in the second level of the indirect contact that is contact with bags or packaging containing the packaged foods.

APPLICATION: Surfaces to be bonded must be clean, dry and free from dust.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.