



TECHNICAL DATA SHEET

20/3/14

REF: AS 239AV Low Tack PVC Protection Tape

DESCRIP: A 150 micron high strength black PVC based tape that combines a flexible PVC backing with a pressure sensitive adhesive.

SPEC:	<u>Widths Available:</u>	Sizes upon request	
	<u>Standard Length:</u>	33m	
	<u>Colours</u>	Various colours	
	<u>Thickness:</u>	150µm	±10%
	<u>Film:</u>	PVC	
	<u>Adhesive:</u>	Pressure sensitive rubber adhesive	
	<u>Elongation:</u>	200%	
	<u>Tensile strength:</u>	7.2 min	kg/25mm ²
	<u>Adhesion to steel:</u>	0.60	kg/25mm ²
	<u>Adhesion to backing:</u>	0.45	kg/25mm ²
	<u>Dielectric breakdown:</u>	7.8 min KV	

STORAGE: The tape should be protected against dust and extreme humidity and can be stored under normal room conditions (+8 to 35°C) for maximum of 12 months

USES: Protection of most substrates. Industrial applications. Electrical insulation. The tape protects the surface against the degradations caused by dirt, the scratches and the sings of utensils during the complete cycle of its usage: maintenance, storage, transportation and assembly. It does NOT protect against corrosion, humidity or chemical substances. This tape is not suitable for extreme Thermo-forming.

APPLICATION: Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.