



Adhesive Specialities Ltd
Tickitape House, 31 Bone Lane
Newbury, RG14 5SH
+44(0)1635 49825

TECHNICAL DATA SHEET

18/11/15

REF: AS 270RJ Single sided PVC foam tape 2mm

DESCRIP: Single sided PVC foam tape high tack solution acrylic adhesive

SPEC:	<u>Widths Available:</u>	Various widths upon request
	<u>Standard Length:</u>	Standard lengths available
	<u>Adhesive type:</u>	Acrylic
	<u>Colours:</u>	Black/White
	<u>Adhesive coat weight:</u>	30 gsm
	<u>Liner type:</u>	80g Amber glassine
	<u>Foam density:</u>	200 Kg per cu. Metre
	<u>Force to compress to 25%:</u>	70 kPa
	<u>Tensile strength:</u> Machine Direction	240 kPa
	<u>Elongation:</u> Machine Direction	140%
	<u>UV resistance</u>	Excellent
	<u>Fungi resistance</u>	Excellent
	<u>Oxidation resistance</u>	Excellent
	<u>Weather resistance</u>	Excellent
	<u>Service temperature</u>	-20°C to +90°C
	<u>Application Temperature</u>	+10°C to +30°C
	<u>Shelf Life</u>	12 months
	<u>Specification</u>	BS7116

Tolerance on widths: ±1.0mm for widths up to & including 19mm
and
±1.5mm for widths greater than 19mm

STORAGE: Normal room temperature

APPLICATION: Surfaces to be bonded must be clean, dry and free from dust.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.