



## TECHNICAL DATA SHEET

18/03/14

**REF:** AS 281AV Co-Ex Low Tack Protection

**DESCRIP:** A low density polyethylene film coated with a rubber based pressure sensitive adhesive.

<b>SPEC:</b>	<u>Film Type</u>	Low density polyethylene (LDPE)
	<u>Adhesive</u>	Rubber
	<u>Colours</u>	Black & White (external side –white)
	<u>Total Thickness:</u>	80 $\mu$ m
	<u>Tensile Strength (longitudinal):</u>	1.2 daN/cm
	<u>Tensile Strength (transversal):</u>	0.9 daN/cm
	<u>Adhesion to Steel:</u>	130 cN/cm
	<u>Elongation (longitudinal):</u>	300 %
	<u>Elongation (Transversal):</u>	400 %
	<u>Unwind Force:</u>	250 cN/cm

**STORAGE** The tape can be stored for 6 months from production date in dry conditions and in its original packaging. Do not expose materials protected with tape to exterior conditions for than 3 months.

**USES:** Self advice film designed for temporary surface protection of aluminum, powder coated aluminum and stainless steel. Do not use on copper, brass and alloys containing copper. Not suitable protection against corrosion, humidity or chemical solvents.

**APPLICATION:** Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. The tape should be protected from dust and other impurities.