

## TECHNICAL DATA SHEET

25/02/15

**REF:** AS305FF Double Sided Skirting Board on Rough Walls

**DESCRIP:** This adhesive film is a highly effective adhesive material from solvent free and aging resistant polyacrylat with balanced characteristics for adhesive strength and shear strength. A polyester scrim serves as stabilization system.

**FEATURES:** It supports a safe bonding and fixing of skirting boards of wood, PVC, and other polar plastics especially for rough material combinations. This product is also suited for laying with higher reset forces where a particularly high pressure sensitive adhesive coat as levelling compound is necessary.

<b>SPEC:</b>	<u>Widths Available:</u>	35, 65, 85m
	<u>Standard Length:</u>	50m
	<u>Adhesive carrier:</u>	Polyester scrim
	<u>Adhesive system:</u>	Acrylic dispersion
	<u>Liner:</u>	Silicon paper, brown
	<u>Thickness (without liner):</u>	440 µm – 460 µm
	<u>Peel adhesion:</u>	≥ 30 N/25mm
	<u>Shear adhesion:</u>	500g /625 mm <sup>2</sup>
	<u>Processing temperature:</u>	+ 5°C to + 30°C
	<u>Temperature Resistance:</u>	-20°C to + 80°C
	<u>Condensation water resistance:</u>	High
	<u>Ageing resistance:</u>	High
	<u>Plasticizer resistance:</u>	High

**STORAGE:** UV protected, dry, room temperature (+23°C)

**USES:** Suitable for mounting skirting-boards on walls.

**APPLICATION:** The surface to be glued should be clean and dry. There should not be any grease, silicone or dust. Apply adhesive tape on the wall. Remove the protective paper. Place the skirting and apply strong pressure.