



Adhesive Specialities Ltd  
Tickitape House, 31 Bone Lane  
Newbury, RG14 5SH  
+44(0)1635 49825

## TECHNICAL DATA SHEET

12/04/17

**REF:** AS 354DR –Double Sided Polyethylene Foam Pads

**DESCRIP:** Double Sided Polyethylene Foam Tape 2mm Thicknesses

<b>SPEC:</b> <u>Widths Available:</u>	All standard widths available other sizes upon request	
<u>Standard Length:</u>	Standard lengths available	
<u>Adhesive:</u>	Rubber/resin	
<u>Tensile strength</u> Machine Direction 265 kPa	400 kPa	Cross Direction
<u>Elongation at break</u> Machine Direction 125%	130%	Cross Direction
<u>Foam density</u>	33 kg per cu metre	
<u>Shore hardness (00scale)</u>	44	
<u>Force to compress to 25%</u>	40 kPa	
<u>Service Temperature:</u>	-20° C to + 70° C	
<u>Application Temperature</u>	+5° C to 25 °C	
<u>UV resistance</u>	Moderate	
<u>Fungi resistance</u>	Excellent	
<u>Weather resistance</u>	Moderate	
<u>Shelf Life</u>	12 months	
<u>Test Method</u>	BS7950:1997	

**STORAGE:** Normal room temperature

**APPLICATION:** Prior to use carefully check that the contact surfaces are totally dry and clean from all traces of oil, grease and dust.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.