



Adhesive Specialities Ltd
Tickitape House, 31 Bone Lane
Newbury, RG14 5SH
+44(0)1635 49825

TECHNICAL DATA SHEET

REF: AS371BA Double Sided Plasticiser Free Tape 27/11/13

DESCRIP: Double sided tape self-adhesive tape with cloth carrier, clear synthetic rubber adhesive, plasticizers-free.

FEATURES: Aggressive adhesive with high tack, high adhesion and good cohesion.

SPEC:	<u>Length of Rolls:</u>	50M
	<u>Widths Available:</u>	38mm - 50mm
	<u>Core Size:</u>	76mm
	<u>Liner:</u>	80g yellow/brown/white two side siliconised paper
	<u>Carrier:</u>	Cloth
	<u>Adhesive:</u>	Clear synthetic rubber, plasticizer free
	<u>Thickness:</u>	255 µm
	<u>Liner Thickness:</u>	70 µm
	<u>Tensile Strength:</u>	22 N/cm
	<u>Elongation at Break:</u>	4 %
	<u>Peel 180°</u>	18 N/cm
	<u>Static Shear</u>	>15 h
	<u>Roller Ball Tack</u>	<3 cm
	<u>Application Temperature:</u>	10°C to +30°C
	<u>Performing Temperature:</u>	-10°C to 50°C
	<u>Short Passage Temperature</u>	-20°C to 50°C

STORAGE: When stored in the original packaging at 21°C and at 50% relative humidity, the product has a shelf life of 12 months.

Uses: Used for vinyl and cushion flooring. Suitable for demanding applications such as metal, wood, metal on metal, etc. with rough or porous surfaces.

APPLICATION: Prior to use carefully check that the contact surfaces are totally dry and clean from all traces of oil, grease and dust.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.