



Adhesive Specialities Ltd
Tickitape House, 31 Bone Lane
Newbury, RG14 5SH
+44(0)1635 49825

TECHNICAL DATA SHEET

18/12/13

REF: AS 975 "Glass with Care" Printed Vinyl Tape

DESCRIP: Carton sealing tape, also for printing.

SPEC: Widths Available: 50 mm plus bespoke sizes upon request

Standard Length: 66m & 132m

Base Colours: Clear, white, buff plus others upon request

Thickness: 50µm

Film Thickness 32µm

Backing Unplasticized clear PVC film

Adhesive Natural rubber & hydrocarbon resin

Peel Adhesion: 1.8N/25mm

Tensile Strength: 47 N/25mm

Elongation at Break: 60%

STORAGE: Tape performance is guaranteed within the first 12 months. Keep it in original box and in a dry atmosphere at temperature between 15°C and 25°C.

USES: Carton sealing tape, also for printing. Effective on standard and most recycled cartons.

APPLICATION: Surfaces to be bonded must be clean, dry and free from dust. If necessary clean surfaces sparingly with a ketone free proprietary solvent, allow to dry prior to tape application.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.